

IR 45 Indumaster® Strong

High alkaline dirt-breaker

Fields of application

- For cleaning alkaline-resistant materials, surfaces and floors in industrial and workshop areas.
- Removes sooty, oily and greasy soil.
- Especially suitable for removing rubber abrasion and graphite.

Product advantages/properties

- Excellent and powerful soil-removing action.
- High dispersive capacity for greasy and oily soil.
- Suitable for application with scrubbing dryers and high-pressure cleaning machines.

| Technical data | |
|-------------------------|--|
| pH value | 13 |
| Product colour | green |
| Packing drum sizes/unit | 12 x 1 litre in a carton 10 litre canister 200 litre returnable drum |



IR 45 Indumaster® Strong

High alkaline dirt-breaker

Application and dosage



For industrial applications.



For alkali-resistant floors.



For alkali-resistant materials and surfaces.



Maintenance cleaning:
Normal soil:
100 ml/10 l water.



Heavy soil:
500 ml - 2 l/10 l water.
Rinse with clean water.



Scrubbing dryer:
Maintenance cleaning:
150 - 200 ml/10 l water.
Intensive cleaning:
250 - 500 ml/10 l water.



High-pressure cleaning:
1:5 to 1:10 with water.

Complementary products

For heavy rubber abrasion:
IR 42 Indumaster® Forte

Warning and safety precautions according to EC guidelines

| | |
|------|---|
| Xi | Irritant. |
| R 38 | Irritating to skin. |
| R 41 | Risk of serious damage to eyes. |
| S 2 | Keep out of the reach of children. |
| S 26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S 28 | After contact with skin, wash immediately with plenty of water |
| S 39 | Wear eye/face protection. |
| S 46 | If swallowed, seek medical advice immediately and show container or label. |

For further safety precautions, please refer to the Material Data Sheet for IR 45 Indumaster® Strong at www.buzil.com.

Important information

Test material to be treated for colourfastness and compatibility on an inconspicuous area before general use.

Use cold water only.

When being used in the automat, the tanks should be regularly cleaned and rinsed.

GISBAU-CODE: GG 60

Article number:

IR45-0001

IR45-0010

IR45-0200

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology.

Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

Version/Printing number TDIR45/4/12